

Laundry machines for Universal applications



Washing machines
Tumble dryers
Rotary irons

Typically Miele

We offer laundry solutions for:

Laundrettes
Hotels
Restaurants
Residential Health Care
Holidays homes
Nursing homes
Camp Sites
Equestrian
Emergency services
Sports & Fitness centres
Mop cleaning
Contract cleaning
Apartments blocks
Student Accommodation
Guests Houses
Pharmaceuticals
& many more

Professional solutions for professional users: Miele has been leading the field in developing washer-extractors and cleaning processes for over a century. As well as versatile machine systems for in-house laundries, adaptable to every size of business, the product range includes practical accessories, as well as professional dishwashers for all daily dishwashing requirements. A complete service from just one source.

Miele Professional's system solutions offer sophisticated washer-extractors and tumble dryers perfectly matched in output and economy for capacities ranging from 6.5 kg to 32 kg, complemented by rotary ironers for the perfect finish: innovative technology for individual requirements.

INNOVATION M is the latest generation of Miele professional machines. The new machines incorporate patented technology such as the MIELE HONEYCOMB DRUM for maximum longevity of your expensive linen, the new SHIELD style front design, and state-of-the-art MIELE intelligence with the new freely programmable PROFITRONIC M controls. This innovative technology also ensures even greater economy. The new generation machines are all designed to perform thousands of problem-free programme cycles effortlessly.

Miele laundry machines offer high tech, high quality that is made in Germany. Product development and production are carried out in compliance with the quality standards set by DIN EN ISO 9001.





The Miele laundry system: Entry level machines

Suggested applications:

Small Hotels
Bed & Breakfasts
Guesthouses
Laundrettes
Apartment Blocks
Student Accommodation
Hostels
Contract Cleaning
Mop Cleaning
Hair Saloons
Camp Sites
Holiday Homes
Fitness Centres
Sports Clubs
& many more

Professional laundry care with Miele begins with a capacity of as little as 6.5 kg. Even at this size, there is a complete system of appliances designed to complement each other and give ideal handling for all types of fabric. Miele's powerful LITTLE GIANTS are the perfect solution for in-house laundries that need to handle different types of laundry quickly and also for establishments where personal laundry is washed alongside the commercial table, bed, bathroom and kitchen linen. Small hotels and guesthouses, restaurants and holiday homes in particular will benefit from the advantages of this system.

The patented Miele HONEYCOMB DRUM guarantees that even the small washer-extractors offer optimum fabric protection in every programme. The intelligent controls with 23 fixed programmes (including a woollens programme for handwashable wool) and a delay start function ensure ease of use and short running times (eg. only approximately 60 minutes for a Cottons 60°C programme). The compact design of the machines means only a minimum of space is required: the washer and dryer can be stacked, while the rotary ironer can be placed against a wall.

Output example:

A small guesthouse with ten beds where the linen is changed three times a week produces approximately 100 kg of laundry, which means carrying out eighteen cycles of 5.5 kg every week (or three cycles a day): the ideal amount for Miele's entry level machines with 6.5 kg capacity – the PW 5065 washer-extractor and PT 5136 tumble dryer.

In this example, the amount of linen that requires ironing (approximately 60%) will be 60 kg per week – an amount that an HM 21-100 rotary ironer with a capacity of 14 kg/h can easily process in 4.5 hours.

Washing and drying in 0.5 m²



PW 5065 washer-extractor with Miele's patented HONEYCOMB DRUM



Washer-extractors

6.5 and 7.5 kg capacity

Model number	PW 5065	PW 6065	W 6073	W 6071
Capacity [kg]	6.5	6.5	7.5	7.5
HONEYCOMB DRUM, volume [l]	51	59	73	73
Spin speed [max. rpm]	1400	1400	1200	1200
G-factor	526	526	450	450
Residual moisture [%]	49	49	51	51
Controls/programmes				
MULTITRONIC 23 programmes	–	–	•	–
PROFITRONIC, freely programmable	–	•	–	•
NOVOTRONIC programmes	•	–	–	–
Plumbing				
Cold water, 1/2" with 3/4" threaded union	1 x	1 x	1 x	1 x
Hot water, 1/2" with 3/4" threaded union	1 x	1 x	1 x	1 x
Drain pump or dump valve	DN22/DN70	DN22/DN70	DN22/DN50	DN22/DN50
Electrical connection				
Three phase asynchronous motor with frequency converter	–	–	•	•
3 N AC 400V 50Hz	–	–	–	–
3 N AC 380–415V 50Hz	–	–	•	•
2N AC 400 V 50 Hz	•	•	–	–
AC 230 V 50 Hz	•	•	–	–
Heater rating [kW]	5.3	5.3	8	8
Total connected load [kW]	5.3	5.5	8.5	8.5
Fuse rating [A]	2 x 16	2 x 16	3 x 16	3 x 16
Can be converted to AC 230V 50Hz	–	–	–	–
Heater rating [kW]	–	–	–	–
Total connected load [kW]	–	–	–	–
Fuse rating [A]	1 x 30	1 x 30	–	–
Heating electric (EL)	EL	EL	EL	EL
Detergent dispenser				
3 compartment dispenser in front of machine	–	–	–	–
4 compartment dispenser in lid of machine	–	–	•	•
Optional extras				
Dispenser for liquid agents	–	–	•	•
Serial interface RS 232	–	–	–	•
Dimensions, weight				
External dimensions H/W/D [mm]	850/595/715	850/595/715	1020/730/790	1020/730/780
Weight [kg]	117	117	147	147
Stackable	•	•	–	–
External finish				
Lid	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Front	White ² or Stainless steel	White ² or Stainless steel	Stainless steel	Stainless steel
Sides	White ² or Stainless steel	White ²	Octo blue ¹	Octo blue ¹
Rear	White ² or Stainless steel	White ²	Galvanized	Galvanized
¹ Powder coated				
² Enamelled				

Tumble dryers

6.5 and 7.5 kg capacity

Model number	PT 5135 C	PT 5136	T 6185
Capacity [kg]	6.5	6.5	7.5
Drum volume [l]	130	130	185
Vented dryer with air recycling system	–	•	•
Controls/programmes			
MULTITRONIC			–
Programmable TROCTRONIC, 9 sensor programmes, 2 timed programmes	•	•	•
Electrical connection			
3 N AC 380–415 V 50 Hz	2 N AC 400 x 50 Hz	2 N AC 400 x 50 Hz	•
AC 220–240 V 50 Hz	•	–	–
Heater rating [kW]	3.45	6.14	8.1
Total connected load [kW]	3.75	6.44	8.55
Fuse rating [A]	1 x 13	1 x 30	3 x 16
Heating options , Electric (EL), Gas (G)	EL	EL	EL
Exhaust ducting			DN100
Peak load cut-out			• (Optional)
Dimensions, weight			
External dimensions H/W/D [mm]	850/595/700	850/595/701	1020/730/725
Weight [kg]			75
Stackable	•	•	–
External finish			
Lid	White, Stainless steel ³	White, Stainless steel ³	Octo blue ¹ , Stainless steel ³
Front	White, Stainless steel ³	White, Stainless steel ³	Octo blue ¹ , Stainless steel ³
Sides	White, Stainless steel ³	White, Stainless steel ³	Octo blue ¹
Rear			Galvanized
¹ Powder coated, ² Enamelled, ³ Optional			

Model number	T 6185 (Gas)	T 6251	T 6351
Capacity [kg]	7.5	10	14
Drum volume [l]	185	250	350
Vented dryer with air recycling system	•	•	•
Controls/programmes			
TROCTRONIC, 9 sensor programmes, 2 timed programmes	•	•	•
Electrical connection			
3 N AC 380–415 V 50 Hz	–	•	•
Heater rating [kW]	6.5 (G 20) 5.4 (G 25)	13.5	18
Total connected load [kW]	0.5	14.3	19.5
Fuse rating [A]	1 x 10	2 x 25	3 x 35
Heating options			
Electric (EL), Gas (G), Steam ³ (HD)	G	EL, G	EL, G, HD
Air intake/exhaust ducting	DN 100	DN 150	DN 150
Dimensions, weight (electric heating)			
External dimensions H/W/D [mm]	1020/730/725	1390/900/814	1390/900/1039
Weight [kg]	75	147	168
External finish			
Lid and front ²	Stainless steel ³	Octo blue ¹	Octo blue ¹
Sides	Octo blue ¹	Octo blue ¹	Octo blue ¹
Rear	Galvanized	Galvanized	–
¹ Powder coated, ² Enamelled, ³ Optional			